## NB1U-EC252D4C 1U Rack-mount Server



Form Factor	393.2 x 430 x 43.5mm (1U)
Processor	(1) Intel <sup>®</sup> Xeon <sup>®</sup> E-2300 Series Processor
Chipset	Intel <sup>®</sup> C252 chipset
Memory	(4) DDR4 3200/2666 ECC UDIMM slots
Storage	(2) 3.5" Fixed HDD
	(2) 2.5" Fixed HDD
SATA Controller	Intel® C252: 6 x SATA3 6.0Gb/s; support RAID 0, 1, 5, 10
Expansion Slots	(1) PCle 4.0 x16
Network	(2) Intel® i210 1GbE RJ45 port
	(1) Realtek RTL8211E 1GbE RJ45 Dedicated port for Management
Integrated Graphics	Aspeed AST2500 256MB DDR4 VRAM
Rear I/O	(4) USB 3.2 Ports
	(1) VGA Port
	(2) 1GbE RJ45 Ports
	(1) Dedicated LAN
	(1) Serial Port
	(1) UID Button/LED
	(1) HDMI
Front I/O	(2) USB 2.0 Ports
Power Supply	(1) Fixed 315W Flex PSU
Server Management	IPMI v2.0 compliant, on board "KVM over IP" support
Environment	Operating temperature: 10°C ~ 35°C /
	Non-operating temperature: -40°C ~ 70°C

Note: No Rail-kit Required

## Serveron Sdn Bhd

Unit C-6-15, Block C, Southgate Commercial Complex, No. 2, Jalan Dua, Chan Sow Lin, 55200 Kuala Lumpur, Malaysia. Main: 1-700-81-7837 Fax: +603-9226-0771

 Email:
 sales@serveron.com.my
 For more information, please visit
 www.serveron.com.my

© 2023 Serveron Sdn Bhd. All rights reserved. Serveron shall not be liable for technical or editorial errors or omissions contained herein. Serveron makes no representation or warranty regarding third-party products or services. The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Intel, the Intel logo, Xeon, Xeon Inside, Core 17 Inside, Core 15 Inside, and Core 13 Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks

