

NB2U-SPC621D8-2L2T 2U Rack-mount Server



PRODUCT HIGHLIGHTS



Support 1 x 3rd Gen Intel® Xeon® Scalable Processor



Up to 8x 2.5" / 3.5" Disk Bays



On-Board Intel® Rapid Storage RAID 0/1/5/10



KVM over IP Support

Form Factor	661.6 x 449.5 x 87.2mm (2U)	
Processor	(1) Intel® Xeon® Scalable 3 rd Gen Processor	
Chipset	Intel® C621A chipset	
Memory	(8) DDR4 3200MHz RDIMM/ LRDIMM slots	
Storage	(12) Front Hot-Plug 2.5" / 3.5" Disk Bays (w/ expander board) (2) Fixed 2.5" SATA Disk Bays (7mm)	
SATA Controller	Intel® C621A: 8 x SATA 6.0Gb/s; support RAID 0, 1, 5, 10	
Expansion Slots	(4) HHHL PCIe 4.0 x16 (3) HHHL PCIe 4.0 x8	
Network	(2) Intel® X710 1/10GbE RJ45 ports (2) Intel® i210 1GbE RJ45 port (1) Realtek RTL8211E 1GbE RJ45 Dedicated port for Management	
Integrated Graphics	Aspeed AST2500 16MB DDR4 VRAM	
Rear I/O	(1) UID Button/LED (4) USB 3.2 Ports (2) 1GbE RJ45 Ports	(1) VGA Port (1) Dedicated LAN (2) 10 GbE RJ45 Ports
Front I/O	(1) USB 3.0 Ports	
Power Supply	(2) Hot-plug 800W 80 Plus Platinum PSU	
Server Management	IPMI v2.0 compliant, on board "KVM over IP" support	
Environment	Operating temperature: 10°C ~ 35°C / Non-operating temperature: -40°C ~ 70°C	



Serveron Sdn Bhd

Unit C-6-15, Block C, Southgate Commercial Complex, No. 2, Jalan Dua, Chan Sow Lin, 55200 Kuala Lumpur, Malaysia

Main: 1-700-81-7837 Fax: +603-9226-0771

Email: sales@serveron.com.my For more information, please visit www.serveron.com.my



Assembled in Malaysia