NBL-SPC621D8-2L2T Enterprise Workstation



Form Factor	760.4 x 200 x 502.9mm	
Processor	(1) Intel® Xeon® Scalable 3 rd Gen Processor	
Chipset	Intel® C621A chipset	
Memory	(8) DDR4 3200MHz RDIMM/LRDIMM slots	
Storage	(7) Hot-plug 2.5"/3.5" SATA/SAS Disk Bays * optional add-on	
SATA Controller	Intel® C621A: 8 x SATA 6.0Gb/s; support RAID 0, 1, 5, 10	
Expansion Slots	(4) FHFL PCIe 4.0 x16	
	(3) FHFL PCIe 4.0 x8	
Network	(2) Intel® X710 1/10GbE RJ45 ports	
	(2) Intel® i210 1GbE RJ45 ports	
	(1) Realtek RTL8211E 1GbE RJ45 Dedicated port for Management	
Integrated Graphics	Aspeed AST2500 16MB DDR4 VRAM	
Rear I/O	(1) UID Button/LED	(1) DB15
	(4) USB 3.2 Ports	(2) 10 GbE RJ45 Ports
	(2) 1GbE RJ45 Ports	(1) Dedicated IPMI
Front I/O	(2) USB 3.0 Ports	
Power Supply	(1) Fixed PSU or	
	(2) Hot-plug 1200W/1600W/2000W 80 Plus Platinum PSU	
Server Management	IPMI v2.0 compliant, on board "KVM over IP" support	
Environment	Operating temperature: 10°C ~ 35°C /	
	Non-operating temperature: -40°C ~ 70°C	

Serveron Sdn Bhd

Unit C-6-15, Block C, Southgate Commercial Complex, No. 2, Jalan Dua, Chan Sow Lin, 55200 Kuala Lumpur, Malaysia Main: 1-700-81-7837 Fax: +603-9226-0771

Email: sales@serveron.com.my For more information, please visit www.serveron.com.my

© 2024 Serveron Sdn Bhd. All rights reserved. Serveron shall not be liable for technical or editorial errors or omissions contained herein. Serveron makes no representation or warranty regarding third-party products or services. The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Intel, the Intel logo, Xeon, Xeon Inside, Core ia Inside, and Core ia Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others.

