


NBE-ROME82T-PLG Enterprise Tower Server



FEATURES



Support 1 x AMD EPYC™ 7003/7003 Processor



High Storage Flexibility with up to 8 disk bays



Redundant Power Supply

Form Factor	589.7 x 200 x 430 mm
Processor	(1) AMD EPYC™ 7452 Processor
Chipset	AMD EPYC
Memory	(8) DDR4 3200 RDIMM, LRDIMM slots
Storage	(8) 3.5" Hot-plug HDD bays
SATA Controller	AMD EPYC 7003/7002 (10 SATA 6.0 Gb/s, support RAID 0,1,5,10) (2) PCIe 4.0 x4 M.22280 Slots
Expansion Slots	(6) PCIe 4.0 x16
Network	(2) 10GbE RJ45 ports (Intel® X550-AT2) (1) Realtek RTL8211E 1GbE RJ45 Dedicated port for Management
Integrated Graphics	ASPEED AST2500 512MB DDR4 video memory
Rear I/O	(1) UID Button (2) USB 3.2 Gen 1 Ports (1) USB 3.2 Gen 2 Port (1) VGA Port (1) Serial Port (2) 10GbE RJ45 Ports (1) 1GbE RJ45 IPMI Port
Front I/O	(2) USB 3.0 Ports
Power Supply	1+1 1600W 80Plus Platinum Hot-plug PSU
Server Management	IPMI v2.0 compliant, on board "KVM over IP" support
Environment	Operating temperature: 10°C ~ 35°C / Non-operating temperature: -40°C ~ 70°C



Serveron Sdn Bhd

Unit C-6-15, Block C, Southgate Commercial Complex, No. 2, Jalan Dua, Chan Sow Lin, 55200 Kuala Lumpur, Malaysia

Main: 1-700-81-7837 Fax: +603-9226-0771

Email: sales@serveron.com.my For more information, please visit www.serveron.com.my

©2024 Serveron Sdn Bhd. All rights reserved. Serveron shall not be liable for technical or editorial errors or omissions contained herein. Serveron makes no representation or warranty regarding third-party products or services. The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. AMD, AMD EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc. Other company, product, and service names may be trademarks or service marks of others.



Assembled in Malaysia